

Drawing number	Model	L	L1	LG	C	BB	Weight (kg)
OEG-300-279	EG280-250N3	1098	580.6	488	472.6	370	814
OEG-300-278	EG280-230N3	1038	520.6	458	432.6	290	732
OEG-300-277	EG280-220N3				432.6		730
OEG-300-276	EG280-200N3	1018	500.6	448	432.6	290	704
OEG-300-275	EG280-180N3	998	480.6	438	432.6		677
OEG-300-274	EG280-160N3	933	415.6	406	402.6	230	593
OEG-300-273	EG280-150N3				402.6		591
OEG-300-280	EG280-140N3				402.6		589
OEG-300-272	EG280-120N3	888	370.6	383	382.6	190	531

可选连接法兰和驱动盘片SAE号 (FLANGE&COUPLING)

	SAE 11.5	SAE 14	SAE 18
SAE 0		●	●
SAE 0.5		●	
SAE 1	●	●	
SAE 2	●		
SAE 3	●		


可选驱动盘片SAE号和尺寸 (OPTION COUPLING DIMENSION)

	V	AN	n	d2	D2
SAE 11.5	352.3	39.6	8	11	333.38
SAE 14	466.6	25.4	8	13.5	438.15
SAE 18	571.4	15.7	12	17	542.92

⊗ = CENTER OF GRAVITY
 DIMENSION IN mm
 OPTION TO IP21 OR IP23

可选连接法兰SAE号和尺寸 (OPTION FLANGE DIMENSION)

	U	m	d1	D1	β	D	h
SAE 0	647.7	16	13.5	679.5	11.25°	710	75
SAE 0.5	584.2	12	13.5	619.13	15°	650	45
SAE 1	511.18	12	12.5	530.23	15°	586	13
SAE 2	447.68	12	11.5	466.73	15°	586	13
SAE 3	409.57	12	11.5	428.63	15°	586	13

DESIGNED BY	COLLATED BY	APPROVED BY	DATE 2020.8.18	PROPORTION 1:7
 ENGGA GENERATORS CO., LTD			EG280-120~250N3 Single Bearing Drawing	
			REV. MARK	