



| 型号 (MODEL) | L | L1 | LG | C | BB | Weight | L(PMG) | L1(PMG) | Weight (PMG) |
|------------|--------|------|-----|-----|-----|--------|--------|---------|--------------|
| EG355-450N | 1153.5 | 1124 | 496 | 384 | 340 | 1280 | 1286.5 | 1257 | 1298 |
| EG355-500N | 1223.5 | 1194 | 516 | 419 | 340 | 1420 | 1356.5 | 1327 | 1438 |
| EG355-560N | 1313.5 | 1284 | 546 | 464 | 340 | 1600 | 1446.5 | 1417 | 1618 |
| EG355-600N | 1333.5 | 1304 | 556 | 464 | 340 | 1678 | 1466.5 | 1437 | 1696 |

可选连接法兰和驱动盘片SAE号 (FLANGE & COUPLING)

| | SAE 14 | SAE 18 |
|---------|--------|--------|
| SAE 0 | ● | ● |
| SAE 0.5 | ● | |
| SAE 1 | ● | |

可选驱动盘片SAE号和尺寸 (OPTION COUPLING DIMENSION)

| | V | AN | n | d2 | D2 |
|--------|-------|------|----|------|-------|
| SAE 14 | 466.6 | 25.4 | 8 | 13.5 | 438.2 |
| SAE 18 | 571.4 | 15.7 | 12 | 17 | 542.9 |

可选连接法兰SAE号和尺寸 (OPTION FLANGE DIMENSION)

| | U | m | d1 | D1 | β | D | h |
|---------|-------|----|----|-------|---------|-----|----|
| SAE 0 | 647.7 | 16 | 14 | 679.5 | 11° 15' | 748 | 17 |
| SAE 0.5 | 584.2 | 12 | 14 | 619.1 | 15° | 748 | 17 |
| SAE 1 | 511.1 | 12 | 14 | 530.2 | 15° | 748 | 17 |

● = CENTER OF GRAVITY
DIMENSION IN mm
OPTION TO IP21 OR IP23

| DESIGNED BY | COLLATED BY | APPROVED BY | FILENAME | DATE | PROPORTION |
|------------------------------|-------------|-------------|------------------------------|------------|------------|
| Xuzhiqiu | | | | 2013-05-27 | 1:5 |
| ENGGA GENERATORS CO. LTD | | | EG355 Single Bearing Drawing | | |
| | | | OYT-200-241 ~ 243, 318 | | |